

NEW

Dolezych
EINFACH SICHER

DoTEXTreme: Textile lifting slings and grommets made of high-performance fiber (UHMW-PE)

The new textile lifting slings and grommets offer TEXTreme advantages in the truest sense of the word

- Ergonomic working due to up to 60% weight reduction compared to steel lifting slings
- Easy handling by one user only
- Textile material is gentle on sensitive surfaces and user's hands
- Low elongation in working range $\leq 1,4\%$ to WLL
- Particularly abrasion-resistant, thanks to high-performance fiber and UHMW-PE eye protection
- Resistant to chemicals and seawater
- Cannot rust
- Buoyant and 0% water absorption
- Usage-temperature range from -40° to $+70^{\circ}$ celsius
- Noise reducing

Product features

- Made of braided 12-strand fiber ropes
- Fiber: UHMW-PE
- Single yarn coating = improvement of internal and external abrasion resistance and extension of service life
- The eyes are additionally equipped with a protective braid made of UHMW-PE equipped
- With CE marking
- With UKCA marking
- Safety factor 7 (according to DIN EN 1492)
- Color of the rope: grey
- Color of eye: orange
- Ropes ≤ 38 mm are additionally thermofixed

The eyes of our slings are standard protected with UHMW-PE braid!

We can also cover the entire braided rope with an additional UHMW-PE or PES braid on request.

Also a steel thimble can be optionally spliced into the eyes.



DoTEXTreme product range

Here you will find an excerpt of our **DoTEXTreme** product range. Our standard portfolio includes all rope diameters from 16 mm to 120 mm in all designs. Simply ask for the required WLL and length in your desired design.

DoTEXTreme Textile lifting sling

Item no.	Working Load Limit SF 7 in t	Nominal diameter of rope mm	Minimum production length L1 m	Weight kg at minimum production length
34 - 1781 0020	4,9	20	2,8	1,29
34 - 1781 0030	10,2	30	3,7	3,95
34 - 1781 0038	15,4	38	4,5	7,20
34 - 1781 0044	20,0	44	5,0	10,57
34 - 1781 0050	25,0	50	5,5	14,59
34 - 1781 0056	30,5	56	6,1	19,92
34 - 1781 0076	52,4	76	-	-
34 - 1781 0112	104	112	-	-



DoTEXTreme Textile grommet with eyes

Item no.	Working Load Limit SF 7 in t	Nominal diameter of rope mm	Minimum production length L1 m	Weight kg at minimum production length
34 - 1782 0022	10,4	22	1,2	2,91
34 - 1782 0032	20,2	32	1,7	5,54
34 - 1782 0040	29,9	40	2,1	8,00
34 - 1782 0048	41,3	48	2,5	11,12
34 - 1782 0054	50,9	54	2,8	13,93
34 - 1782 0112	185,3	112	-	-

Also available as grommet without eyes.



DoTEXTreme Textile double grommet with eyes

Item no.	Working Load Limit SF 7 in t	Nominal diameter of rope mm	Minimum production length L1 m	Weight kg at minimum production length
34 - 1784 0016	11,8	16	0,5	2,11
34 - 1784 0022	20,9	22	0,7	3,18
34 - 1784 0032	40,4	32	0,9	6,36
34 - 1784 0040	59,9	40	1,1	9,05
34 - 1784 0054	101,9	54	1,5	15,64
34 - 1784 0112	370,7	112	-	-


Also available as grommet without eyes.



Do you have questions about the product?
We will be happy to advise you.

T +49 231 82 85-0
M info@dolezych.de

www.dolezych.de



Dolezych GmbH & Co. KG | Hartmannstr. 8 | 44147 Dortmund